

L660QX3D

698-960 / 1518-2700 / 5150-5850 MHz 3 / 5 / 6 dBi MIMO Omni Antenna

Electrical Specifications

Frequency Range (MHz)	698-960	1518-2700	5150-5850
Horizontal Half-power Beamwidth (°)	360	360	360
Vertical Half-power Beamwidth (°)	70	35	35
Gain (dBi)	3	5	6
Polarization	Vertical (2x)		
Typical VSWR	≤2.5	≤2.0	≤3.5
Average Power, Maximum (W)	50		
Impedance (Ω)	50		



Mechanical Specifications

Dimensions (mm)	Φ78×206
Net Weight (kg)	0.7 (installation kit included)
Radome Material	PVC
Radome Color	White
Cable Length (cm)	35 (1ft)
Connector	N Female (2x)

Environmental Specifications

Application	Outdoor
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)
Humidity (%)	5 to 95
Survival Wind Velocity (m/s)	60

Mounting Specifications

MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED

Mounting Mast Diameter (mm)	Φ 40 to 50
-----------------------------	------------

CELLULAR ANTENNAS
Omni