## L7PB6515FR

## 698-960 MHz 14.5dBi X Pol Panel Antenna

### **Electrical Specifications**

Frequency Range (MHz)	698-960
Horizontal Half-power Beamwidth (°)	<b>65</b> ±5
Vertical Half-power Beamwidth (°)	<b>17</b> ±3
Gain (dBi)	<b>14.5</b> ±1
Polarization	$\pm 45^{\circ}$
Cross-polar discrimination (dB)	≥15(±60° ≥10)
Isolation(dB)	≥25
Front to Back Ratio (dB)	≥25
VSWR	≤1.5
Average Power, Maximum (W)	200
Impedance (Ω)	50



## Environmental Specifications

**Mechanical Specifications** 

Dimensions (mm)

Net Weight (kg)

Connector

Environmental Specifications	
Outdoor	
-40 to +70 (-40 to 158°F)	
5 to 95	
60	

# Radition Pattern

## **Mounting Specifications**

MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED

Mounting Mast Diameter (mm)

Φ 50 to 115

1200×450×150

25(installation kit included)

**4×N** Female

Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com

©2019 Decipro Technologies. All Rights Reserved. 2023

Specifications may be changed without notice.

Revision Date: 12 December