

L727PB651215FR

698-960/1695-2690 MHz 12/14.5dBi X Pol Panel Antenna



Electrical Specifications

Frequency Range (MHz)	698-960	1695-2690
Horizontal Half-power Beamwidth (°)	65 ± 5	65 ± 5
Vertical Half-power Beamwidth (°)	33 ± 3	17 ± 3
Gain (dBi)	12 ± 1	14.5 ± 1
Polarization	±45°	
Cross-polar discrimination (dB)	≥15(±60° ≥10)	
Isolation(dB)	≥25	
Front to Back Ratio (dB)	≥25	
VSWR	≤1.8	
Average Power, Maximum (W)	200	
Impedance (Ω)	50	



Mechanical Specifications

Dimensions (mm)	1150×450×150
Net Weight (kg)	15(installation kit included)
Connector	4×N Female

Environmental Specifications

Application	Outdoor
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)
Humidity (%)	5 to 95
Survival Wind Velocity (m/s)	60

Mounting Specifications

MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED

Mounting Mast Diameter (mm)	Φ 50 to 115
-----------------------------	-------------

Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226
Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com