L727DS10BNK

698-960 / 1710-2700 MHz 10 / 11dBi Log Periodic Antenna

| Electrical Specifications | | | |
|-------------------------------------|----------|-----------|-----------|
| Frequency Range (MHz) | 698-960 | 1710-2500 | 2500-2700 |
| Horizontal Half-power Beamwidth (°) | 75 | 75 | 60 |
| Vertical Half-power Beamwidth (°) | 50 | 50 | 40 |
| Gain (dBi) | 10 | 10 | 11 |
| Polarization | Vertical | | |
| Front to Back Ratio (dB) | ≥15 | ≥18 | ≥20 |
| VSWR | ≤2.0 | ≤2.0 | ≤2.0 |
| Average Power, Maximum (W) | 100 | | |
| Impedance (Ω) | 50 | | |

| Mechanical Specifications | | |
|---------------------------|---------------------------------|--|
| Dimensions (mm) | 445×205×38 | |
| Packing Dimension (cm) | 53×47×49 (10pcs/carton) | |
| Net Weight (kg) | 1.1 (installation kit included) | |
| Cable Length (cm) | 30 | |
| Connector | N Female | |

| Environmental Specifications | | |
|--|---------------------------|--|
| Application | Outdoor | |
| Operating Temperature ($^\circ \!\!\! \mathbb{C}$) | -40 to +70 (-40 to 158°F) | |
| Humidity (%) | 5 to 95 | |
| Survival Wind Velocity (m/s) | 60 | |

| Mounting Specifications | | |
|---|------------|--|
| MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED | | |
| Mounting Mast Diameter (mm) | Φ 40 to 50 | |

Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com



