

## 5G LTE WiFi Multiband Combination Antenna, 4 Leads

### Electrical Specifications

Cable Leads Number	Cable 1 - 2 (4G/5G Elements)		Cable 3 - 4 (WiFi Elements)	
Frequency Range(MHz)	617-960 / 1690-6000		2400-2500/4900-6000	
Peak Gain (dBi)	617-960MHz	4	2400-2500 MHz	5
	1690-2700MHz	6	4900-6000 MHz	6
	3300-4200MHz	7		
	4900-6000MHz	8		
Isolation (dB)	>10		>12	
Polarization	Vertical		Vertical	
VSWR	≤2.0		≤2.0	
Average Power, Maximum (W)			10	
Impedance (Ω)			50	

### Mechanical Specifications

Dimensions (mm)	Φ175×80 (7" Dia. × 3.15" High)		
Net Weight (kg)	1.8		
Radome Material / Color	UV Stabilized ABS / Black or White		
Cable Type / Length (M)	RG58 / 5 (17ft)		RG58 / 5 (17ft)
Connector Type	SMA Female (2×)		SMA Female (2×)

### Environmental Specifications

Application	Indoor / Outdoor
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)
Water Ingress Rating	IP69K

