CB21YA

LTE / CBRS / GPS Multiband MIMO Combination Antenna, 3 Leads

Electrical Specifications			
Cable Leads Number	Cable 1 & 2 (LTE)	Cable 3 (GPS)	
Frequency (MHz)	698-960 / 1710-3800	1575.42±2 MHz	
Gain (dBi)	2/3	5 (28dB with LNA)	
Polarization	Vertical	RHCP	
VSWR	≤2.5 / ≤2.5	≤2.0	
Noise Figure (dB)	N/A	2.0 max, 1.7 typical	
Current (mA)	N/A	20 max, 10 typical	
Amplifier Bias	N/A	2.7 to 5 VDC	
Average Power, Maximum (W)	1	10	
Impedance (Ω)	50		



Defipro

Mechanical Specifications			
Dimensions (mm)	Φ7	Φ 75 × 25	
Net Weight (kg)	(0.3	
Radome Material	UV Stab	UV Stabilized ABS	
Radome Color	В	Black	
Cable Type	RG58	RG174	
Cable Length (CM)	457	457	
Connector	SMA Male (2×)	SMA Male (1×)	

Environmental Specifications		
Application	Indoor / Outdoor	
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)	
Humidity (%)	5 to 95	
Water Ingress Rating	IP67	

Mounting Specifications		
MOUNTING ACCESSORIES ARE INCLUDED UNLESS OTHERWISE SPECIFIED		
Mounting Style	Surface Mount	
Mounting Accessories	Surface Mount Nut and Washer	

Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com