

## 4900-5850 MHz 29.5dBi Grid Antenna

Electrical Specifications	
Frequency Range (MHz)	4900-5850
Horizontal Half-power Beamwidth (°)	4
Vertical Half-power Beamwidth (°)	6
Gain (dBi)	29.5
Polarization	Vertical and Horizontal
VSWR	≤1.5
Front to Back Ratio (dB)	≥25
Average Power, Maximum (W)	100
Impedance (Ω)	50



Mechanical Specifications		
Dimension (cm)	60 × 90	
Net Weight (kg)	4.5 (installation kit included)	
Connector	N Female (1×)	

Environmental Specifications	
Application	Outdoor
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)
Humidity (%)	5 to 95
Survival Wind Velocity (km/h)	200

Mounting Specifications  MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED	
Mounting Mast Diameter (mm)	Φ 40 to 50

Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com