

4900-5850 MHz 22dBi Grid Antenna

Electrical Specifications		
Frequency Range (MHz)	4900-5850	
Horizontal Half-power Beamwidth (°)	9	
Vertical Half-power Beamwidth (°)	12	
Gain (dBi)	22	
Polarization	Vertical and Horizontal	
VSWR	≤1.5	
Front to Back Ratio (dB)	≥20	
Average Power, Maximum (W)	100	
Impedance (Ω)	50	



Mechanical Specifications		
Dimension (cm)	30 × 40	
Net Weight (kg)	1.4 (installation kit included)	
Connector	N Female (1×)	

Environmental Specifications		
Application	Outdoor	
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)	
Humidity (%)	5 to 95	
Survival Wind Velocity (km/h)	200	

Mounting Specifications MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED	
Mounting Mast Diameter (mm)	Φ 40 to 50

Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com