WXBP06D30



5650-6450 MHz Dual Polarization 29.5dBi 2 Feet Dish Antenna

Electrical Specifications	
Frequency Range (MHz)	5650-6450
Horizontal Half-power Beamwidth (°)	5
Vertical Half-power Beamwidth (°)	5
Gain (dBi)	29.5
Polarization	Vertical and Horizontal
VSWR	≤1.5
Front to Back Ratio (dB)	≥35
Ports Isolation (dB)	≥28
Average Power, Maximum (W)	100
Impedance (Ω)	50
Lightning Protection	DC Ground



Mechanical Specifications		
Dish Diameter (cm)	60	
Packing Dimension (mm)	73 × 70 × 18	
Net Weight (kg)	5.5 (installation kit included)	
Packing Weight (kg)	8.7	
Connector	N Female (2×)	

Environmental Specifications	
Application	Outdoor
Operating Temperature ($^{\circ}\mathbb{C}$)	-40 to +70 (-40 to 158 $^{\circ}\mathrm{F}$)
Humidity (%)	5 to 95
Survival Wind Velocity (km/h)	200

Mounting Specifications		
MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED		
Mounting Style	Pole Mount	
Mounting Mast Diameter (mm)	Φ 50 to 75	

Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com