

## 138-174 MHz 4 Elements Exposed Dipole Antenna, Half Wave Design, Bi-Directional Patterns

Electrical Specifications	
Frequency Range (MHz)	138-174
Bandwidth (MHz)	36
Pattern	Bi-directional
Vertical Half-power Beamwidth (°)	17
Gain (dBi)	10.1
Polarization	Vertical
VSWR	≤1.8
Boom Wave Length Spacing	1/2 λ
Average Power, Maximum (W)	300
Impedance (Ω)	50
Lightning Protection	DC Ground

Mechanical Specifications	
Length (cm)	570
Net Weight (kg)	25.5 (installation kit included)
Radiator Material	Aluminum Alloy
Number of Radiators	4
Connector	N Female or Customized

Environmental Specifications	
Application	Outdoor
Operating Temperature (°C)	-40 to +70 (-40 to 158 $^{\circ}\mathrm{F}$ )
Humidity (%)	5 to 95
Survival Wind Velocity (km/h)	160

Mounting Specifications		
MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED		
Mounting Mast Diameter (mm)	Φ 40 to 50	

Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com