


## 138-174 MHz 8 Elements Exposed Dipole Antenna, Quarter Wave Design, Offset Patterns

Electrical Specifications	
Frequency Range (MHz)	138-174
Bandwidth (MHz)	36
Horizontal Half-power Beamwidth (°)	210
Vertical Half-power Beamwidth (°)	18
Gain (dBi)	13
Polarization	Vertical
VSWR	≤1.5
Boom Wave Length Spacing	1/4 λ
Average Power, Maximum (W)	300
Impedance (Ω)	50
Lightning Protection	DC Ground

Mechanical Specifications	
Length (cm)	1150
Net Weight (kg)	40 (installation kit included)
Radiator Material	Aluminum Alloy
Number of Radiators	8
Connector	N Female or Customized

Environmental Specifications	
Application	Outdoor
Operating Temperature (°C)	-40 to +70 (-40 to 158 $^{\circ}\mathrm{F}$ )
Humidity (%)	5 to 95
Survival Wind Velocity (km/h)	160

Mounting Specifications	
MOUNTING BRACKETS ARE INCLUDED UNLESS O	THERWISE SPECIFIED
Mounting Mast Diameter (mm)	Φ 40 to 50
Pattern	



Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com