

## 3300-3800 MHz 8dBi Omni Antenna, N Female

Electrical Specifications	
Frequency Range (MHz)	3300-3800
Horizontal Half-power Beamwidth (°)	360
Vertical Half-power Beamwidth (°)	17
Gain (dBi)	8
Polarization	±45
VSWR	≤2.0
Average Power, Maximum (W)	100
Impedance (Ω)	50

1	4


Mechanical Specifications		
Dimensions (mm)	Ф20×350	
Net Weight (kg)	0.45(installation kit included)	
Radome Material	Fiberglass	
Radome Color	Gray	
Connector	SMA Female	


Environmental Specifications		
Application	Outdoor	
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)	
Humidity (%)	5 to 95	
Survival Wind Velocity (m/s)	60	

## **Mounting Specifications**

MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED

Mounting Mast Diameter (mm) Φ 30 to 50





Decipro Technologies Ltd., B2A Building, New Light Industrial Base, Luocun S Ave. Nanhai, Foshan, Guangdong, China 528226 Tel +86(0)757 8355 4087 Email sales@deciprotech.com Website www.deciprotech.com